


Karta techniczna / Technical data sheet Puszka PET / CAN PET 250_HF_sleek



-	<i>Product</i>	<i>Can 250_HF_sleek</i>	
-	<i>Number</i>	<i>27596-0</i>	
-	<i>Closure type</i>	<i>202</i>	
-	<i>Volume</i>	<i>250 (ml)</i>	<i>8,45 (oz)</i>
A	<i>The outer diameter</i>	<i>57,6 ± 0,5 (mm)</i>	<i>2,268 ± 0,02 (in)</i>
G	<i>The height of empty cans</i>	<i>144 ± 0,5 (mm)</i>	<i>5,669 ± 0,02 (in)</i>
D	<i>The diameter of the flange</i>	<i>57,3 + 0,5 (mm)</i>	<i>2,256 + 0,02 (in)</i>
F	<i>The thickness of the flange</i>	<i>0,30 + 0,05 (mm)</i>	<i>0,012 + 0,002 (in)</i>
P	<i>The diameter of the base ring</i>	<i>40 ± 0,5 (mm)</i>	<i>1,575 ± 0,02 (in)</i>
C	<i>The height of the socket</i>	<i>12,5 ± 0,5 (mm)</i>	<i>0,492 ± 0,02 (in)</i>
U	<i>Fill level</i>	<i>15 ± 1 (mm)</i>	<i>0,591 ± 0,04 (in)</i>
T	<i>Push up height</i>	<i>14,7 ± 0,5 (mm)</i>	<i>0,579 ± 0,02 (in)</i>
W	<i>Inner flange diameter</i>	<i>52,3 max. (mm)</i>	<i>2,059 max. (in)</i>
-	<i>Resistance to axial pressure</i>	<i>67,3 (kg)</i>	<i>148,37 (lb)</i>
-	<i>Resistance to internal pressure</i>	<i>1,5 (bar)</i>	<i>21,76 (psi)</i>
-	<i>The nominal weight of the cans (no closure)</i>	<i>26,5 ± 0,8 (g)</i>	<i>0,0584 ± 0,0018 (lb)</i>
-	<i>Date / Rev A</i>	<i>2016-11-18</i>	

PET CAN TECH

Karta techniczna / Technical data sheet
Puszka PET / CAN PET 250_HF_sleek

